



# CCV Edge IM15

Unattended self-service  
payment terminal for  
contactless payments



**PIN on glass** | prevents consumers  
from 'can't pay situations' as it enables  
contactless payments with PIN on demand



**Compact** | the all-capabilities terminal  
design fits even into small machines and  
into standard cut-outs



**Adaptable** | terminal can be installed  
flexibly, in landscape or portrait format



**Connectivity** | it connects anywhere with  
its multiple built-in interfaces and optional  
4G interface for remote locations



<b>Display</b>	3.5" TFT LCD 480 x 320 Touch Screen   600 nits   Supports PIN on Glass   front-glass hardness 6 Mohs
<b>Card Readers</b>	Contactless
<b>Scanner</b>	Reads 1D & 2D codes
<b>Memory</b>	512 MB Flash + 512 MB DDR RAM
<b>Keys / buttons</b>	1 x Reset key (rear)
<b>Audio</b>	1 Speaker (side)
<b>Dimensions</b>	108,4x75x43mm (WxHxD), 108,4x75x18,5mm (WxHxD) outside the machine, 72x60x24,5mm (WxHxD) within the machine (without cables and mounting accessories)
<b>Front plane cut-out</b>	73 x 61mm, EVA EPS CDM compliant
<b>Connectivity</b>	1 x USB Host (USB-A)   1 x USB Device (USB-C)   1 x LAN   1 x RS232   1 x MDB WiFi 5 GHz   Bluetooth 5.0 4G RF Modem (optional)
<b>Power supply</b>	7 - 48 VDC via main power supply, MDB, or RS232
<b>Power consumption (typ.)</b>	Without 4G modem @ 12 VDC: max 500 mA   75 mA standby   6 mA sleep With 4G modem @ 12 VDC: max 1.5 A   100 mA standby   8 mA sleep
<b>Security</b>	2x Secure Access Module (SAM) slots
<b>Environmental</b>	20°C ~ 70°C ( 4°F ~ 158°F) Operating Temperature 30°C ~ 70°C ( 22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non Condensing IP 65   IK09
<b>Flammability rating</b>	V2 according to UL94, IEC 6069511 10, 20 and IEC 60950 1
<b>Certifications</b>	<b>Payment:</b> EMV Contactless L1   Mastercard PayPass L2   Visa payWave L2   American ExpressPay L2   Discover D PAS L2   Interac_Flash L2   J/Speedy L2   Mastercard TQM   qPBOC L1   qUICS L2 <b>Security:</b> PCI PTS 6.x, SRED   CSEC   UKCC <b>Regulatory:</b> FCC   IC   UL   RoHS   CE   UKCA

All specifications are subject to change and are to be confirmed in the course of the qualification process.